

BEGA**50 086.2**

Wall luminaire for indoor use



Project · Reference number


Date

Product data sheet

Application

Free-radiating wall luminaire · indoor luminaire
made of hand-blown opal glass, satin matt and
metal housing, for all lighting tasks.

Product description

Metal housing
stainless steel finish
Hand-blown opal glass, satin matt
2 mounting holes \varnothing 5 mm
Distance apart 287 x 55 mm
Connecting terminals 2.5[□]
Earth conductor connection
Installation surface 315 x 86 mm
LED-Module for mains voltage
220-230 V \sim 50/60 Hz
BEGA Thermal Switch[®]
Temporary thermal shutdown to protect
temperature-sensitive components
Safety class I
 – Safety mark
CE – Conformity mark
Weight: 1.6 kg

Light technique

Luminaire data for the light planning program
DIALux for outdoor lighting, street lighting and
indoor lighting as well as luminaire data in
EULUMDAT- and IES-format you will find on the
BEGA web page www.bega.com.

Lamp

Luminaire connected wattage 16 W
Rated temperature $t_a = 25$ °C
Ambient temperature $t_{a\max} = 50$ °C



50 086.2 K3

Module designation 2x LED-0662/830
Colour temperature 3000 K
Colour rendering index $R_a > 80$
Module luminous flux 1520 lm
Luminaire luminous flux 1413 lm
Luminaire luminous efficiency 88,3 lm/W

