

**BEGA****50 106.2**

Wall luminaire for indoor use



Project · Reference number

Date

## Product data sheet

### Application

Free-radiating wall LED wall luminaire · indoor luminaire made of hand-blown opal glass, satin matt and metal housing.

The character of the three-ply opal glass creates a smooth and uniform light distribution in the room.

### Product description

Glass holder made of matt brushed aluminium

Hand-blown opal glass, satin matt

2 mounting holes  $\varnothing$  6 mm

Distance apart 160 x 32 mm

Connection terminal 2.5<sup>□</sup>


Earth conductor connection

Installation surface 215 x 60 mm

LED-Module for mains voltage

220-230 V  $\sim$  50/60 Hz

Safety class I

 – Safety mark

**CE** – Conformity mark

Weight: 1.2 kg

### Lamp

Luminaire connected wattage 32 W

Rated temperature  $t_a = 25$  °C

Ambient temperature  $t_{a \max} = 25$  °C

### 50 106.2 K3

Module designation 2x LED-0608/830

Colour temperature 3000 K

Colour rendering index  $R_a > 80$

Module luminous flux 3040 lm

Luminaire luminous flux 2456 lm

Luminaire luminous efficiency 76,8 lm/W

### Service life of the LED

max. ambient temperature  $t_a = 25$  °C

– at 50,000h: L70B50

