

BEGA**50 128**

Wall luminaire for indoor use



Project · Reference number

Date

Product data sheet

Application

Open and free-radiating LED wall luminaire · indoor luminaire with hand-blown opal glass and metal bracket.

The character of the opal glass creates a smooth and uniform light distribution in the room.

Product description

Aluminium bracket,
finish white enamel

Stainless steel glass holding bolts

Hand-blown opal glass

2 mounting holes \varnothing 6.5 mm

Distance apart 95 mm

2 cable entries for through-wiring for mains

cable up to \varnothing 10.5 mm max. $3 \times 1.5^{\square}$

Connection terminal 2.5^{\square}

Earth conductor connection

LED-Module for mains voltage


220-230 V \sim 50/60 Hz

BEGA Thermal Switch[®]

Temporary thermal shutdown to protect

temperature-sensitive components

Safety class I

 – Safety mark

CE – Conformity mark

Weight: 1.2 kg

Lamp

Luminaire connected wattage 16 W

Rated temperature $t_a = 25^{\circ}\text{C}$

Ambient temperature $t_{a\text{max}} = 40^{\circ}\text{C}$

50 128 K3

Module designation 2x LED-0662/830

Colour temperature 3000 K

Colour rendering index $R_a > 80$

Module luminous flux 1520 lm

Luminaire luminous flux 1184 lm

Luminaire luminous efficiency 74 lm/W

