

BEGA**50 132**

Wall luminaire for indoor use



Project · Reference number

Date

Product data sheet

Application

Open and free-radiating LED wall luminaire · indoor luminaire with hand-blown opal glass and metal bracket.

The character of the opal glass creates a smooth and uniform light distribution in the room.

Product description

Aluminium bracket,
finish white enamel

Stainless steel glass holding bolts

Hand-blown opal glass

3 fixing holes \varnothing 6.5 mm

130 x 195 mm spacing

2 cable entries for through-wiring for mains

cable up to \varnothing 10.5 mm max. $3 \times 1.5^{\square}$


Connection terminal 2.5^{\square}

Earth conductor connection

LED-Module for mains voltage

220-230 V \sim 50/60 Hz

Safety class I

 - Safety mark

CE - Conformity mark

Weight: 1.2 kg

Lamp

Luminaire connected wattage

16 W

Rated temperature

$t_a = 25^{\circ}\text{C}$

Ambient temperature

$t_{a \text{ max}} = 50^{\circ}\text{C}$

Service life criteria

50 000 h / L_{70}

50 132 K3

Module designation

LED-0608/830

Colour temperature

3000 K

Colour rendering index

$R_a > 80$

Module luminous flux

1520 lm

Luminaire luminous flux

1329 lm

Luminaire luminous efficiency

83,1 lm/W

