

**BEGA****50 133**

Wall luminaire for indoor use



Project · Reference number

Date

## Product data sheet

### Application

Open and free-radiating LED wall luminaire · indoor luminaire with hand-blown opal glass and metal bracket.

The character of the opal glass creates a smooth and uniform light distribution in the room.

### Product description

Aluminium bracket,  
finish white enamel

Stainless steel glass holding bolts

Hand-blown opal glass

3 fixing holes  $\varnothing$  6.5 mm

180 x 240 mm spacing

2 cable entries for through-wiring for mains

cable up to  $\varnothing$  10.5 mm max.  $3 \times 1.5^{\square}$


Connection terminal  $2.5^{\square}$

Earth conductor connection

LED-Module for mains voltage

220-230 V  $\sim$  50/60 Hz

Safety class I

 - Safety mark

**CE** - Conformity mark

Weight: 1.8 kg

### Lamp

Luminaire connected wattage

32 W

Rated temperature

$t_a = 25^{\circ}\text{C}$

Ambient temperature

$t_{a \text{ max}} = 30^{\circ}\text{C}$

Service life criteria

50 000 h/ $L_{70}$

### 50 133 K3

Module designation

2x LED-0608/830

Colour temperature

3000 K

Colour rendering index

$R_a > 80$

Module luminous flux

3040 lm

Luminaire luminous flux

2556 lm

Luminaire luminous efficiency

79,9 lm/W

