

BEGA**50 137.2**

Wall luminaire for indoor use



Project · Reference number

Date

Product data sheet

Application

Free-radiating wall LED wall luminaire · indoor luminaire made of hand-blown opal glass, satin matt and metal housing.

The character of the three-ply opal glass creates a smooth and uniform light distribution in the room.

Product description

Glass holder made of matt brushed aluminium

Hand-blown opal glass, satin matt

2 mounting holes \varnothing 6 mm

Distance apart 30 mm

Connection terminal 2.5[□]


Earth conductor connection

Installation surface 145 x 35 mm

LED-Module for mains voltage

220-230 V \sim 50/60 Hz

Safety class I

 – Safety mark

CE – Conformity mark

Weight: 0.65 kg

Lamp

Luminaire connected wattage 12 W

Rated temperature $t_a = 25$ °C

Ambient temperature $t_{a \max} = 40$ °C

50 137.2 K3

Module designation LED-0607/830

Colour temperature 3000 K

Colour rendering index $R_a > 80$

Module luminous flux 1080 lm

Luminaire luminous flux 880 lm

Luminaire luminous efficiency 73,3 lm/W

Service life of the LED

Ambient temperature $t_a = 25$ °C

– at 64,000h: L70B50

max. ambient temperature $t_a = 40$ °C

– at 52,000h: L70B50

