

BEGA**50 208**

Wall luminaire for indoor use



Project · Reference number



Date

Product data sheet

Application

Free-radiating LED wall luminaire · indoor luminaire with crystal glass and metal bracket. For all lighting tasks in interior applications. They are ideal for places where a soft and uniform lighting distribution is required.

Product description

Metal housing, finish white enamel
 Crystal glass, inside white
 2 mounting holes \varnothing 4.5 mm
 Distance apart 262 mm
 2 cable entries for through-wiring for mains cable up to \varnothing 10.5 mm max. 3×1.5^2
 Connection terminal 2.5^2
 Earth conductor connection
 LED-Module for mains voltage
 220-230 V \sim 50/60 Hz
 Safety class I
 – Safety mark
 – Conformity mark
 Weight: 3.0 kg

Lamp

Luminaire connected wattage	24 W
Rated temperature	$t_a = 25 \text{ }^\circ\text{C}$
Ambient temperature	$t_{a,max} = 30 \text{ }^\circ\text{C}$
Service life criteria	50 000 h/L ₇₀

50 208 K3

Module designation	2x LED-0607/830
Colour temperature	3000 K
Colour rendering index	$R_a > 80$
Module luminous flux	2160 lm
Luminaire luminous flux	1601 lm
Luminaire luminous efficiency	66,7 lm/W

