

**BEGA****50 211**

Wall luminaire for indoor use



Project · Reference number


Date

## Product data sheet

### Application

Free-radiating LED wall luminaire · indoor luminaire with crystal glass and metal bracket. For all lighting tasks in interior applications. They are ideal for places where a soft and uniform lighting distribution is required.

### Product description

Metal housing, finish white enamel  
 Crystal glass, inside white  
 2 mounting holes  $\varnothing$  4.5 mm  
 Distance apart 262 mm  
 2 cable entries for through-wiring for mains cable up to  $\varnothing$  10.5 mm max.  $3 \times 1.5^2$   
 Connection terminal  $2.5^2$   
 Earth conductor connection  
 LED-Module for mains voltage  
 220-230 V  $\sim$  50/60 Hz  
 Safety class I  
 – Safety mark  
 – Conformity mark  
 Weight: 2.6 kg

### Lamp

Luminaire connected wattage	24 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a,max} = 30$ °C
Service life criteria	50 000 h/L <sub>70</sub>

### 50 211 K3

Module designation	2x LED-0607/830
Colour temperature	3000 K
Colour rendering index	$R_a > 80$
Module luminous flux	2160 lm
Luminaire luminous flux	1533 lm
Luminaire luminous efficiency	63,9 lm/W

