

BEGA**50 255**

Wall luminaire for indoor use



Project · Reference number

Date

Product data sheet

Application

LED wall luminaire · indoor luminaire made of hand-blown opal glass, satin matt and metal fitting, for all lighting tasks.

They are ideal for places where a soft and uniform lighting distribution is required.

Product description

Metal housing, finish
white enamel

Hand-blown opal glass, satin matt

2 mounting holes \varnothing 6 mm

Distance apart 160 mm

1 cable entry for mains supply cable

up to \varnothing 10.5 mm max. 3 x 1.5[□]

Connecting terminals 2.5[□]

Earth conductor connection


LED-Module for mains voltage


220-230 V \sim 50/60 Hz

BEGA Thermal Switch[®]

Temporary thermal shutdown to protect temperature-sensitive components

Safety class I

 – Safety mark

 – Conformity mark

Weight: 1.1 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamp

Luminaire connected wattage 12 W

Rated temperature $t_a = 25$ °C

Ambient temperature $t_{a\max} = 40$ °C

50 255 K3

Module designation LED-0607/830

Colour temperature 3000 K

Colour rendering index $R_a > 80$

Module luminous flux 1080 lm

Luminaire luminous flux 1000 lm

Luminaire luminous efficiency 83,3 lm/W

