

BEGA**50 256**

Wall luminaire for indoor use



Project · Reference number

Date

Product data sheet

Application

LED wall luminaire · indoor luminaire made of hand-blown opal glass, satin matt and metal fitting, for all lighting tasks.

They are ideal for places where a soft and uniform lighting distribution is required.

Product description

Metal housing, finish
white enamel

Hand-blown opal glass, satin matt

2 mounting holes \varnothing 6 mm

Distance apart 220 mm

2 cable entries for through-wiring for mains

cable up to \varnothing 10.5 mm max. $3 \times 1.5^{\square}$

Connecting terminals 2.5^{\square}

Earth conductor connection


LED-Module for mains voltage


220-230 V \sim 50/60 Hz

BEGA Thermal Switch[®]

Temporary thermal shutdown to protect temperature-sensitive components

Safety class I

 – Safety mark

 – Conformity mark

Weight: 2.0 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamp

Luminaire connected wattage 16 W

Rated temperature $t_a = 25^{\circ}\text{C}$

Ambient temperature $t_{a\text{max}} = 40^{\circ}\text{C}$

50 256 K3

Module designation 2x LED-0662/830

Colour temperature 3000 K

Colour rendering index $R_a > 80$

Module luminous flux 1520 lm

Luminaire luminous flux 1237 lm

Luminaire luminous efficiency 77,3 lm/W

