

**BEGA****50 258**

Wall luminaire for indoor use



Project · Reference number

Date

## Product data sheet

### Application

LED wall luminaire · indoor luminaire made of hand-blown opal glass, satin matt and metal fitting, for all lighting tasks.

They are ideal for places where a soft and uniform lighting distribution is required.

### Product description

Metal housing, finish  
white enamel

Hand-blown opal glass, satin matt

2 mounting holes  $\varnothing$  6 mm

Distance apart 200 mm

2 cable entries for through-wiring for mains

cable up to  $\varnothing$  10.5 mm max. 3 x 1.5<sup>2</sup>

Connection terminal 2.5<sup>2</sup>

Earth conductor connection

LED-Module for mains voltage

220-230 V  $\sim$  50/60 Hz

Safety class I

– Safety mark

**CE** – Conformity mark

Weight: 2.2 kg

### Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page [www.bega.com](http://www.bega.com).

### Lamp

Luminaire connected wattage 24 W

Rated temperature  $t_a = 25$  °C

Service life criteria 50 000 h/L<sub>70</sub>

### 50 258 K3

Module designation 2x LED-0607/830

Colour temperature 3000 K

Colour rendering index  $R_a > 80$

Module luminous flux 2160 lm

Luminaire luminous flux 1540 lm

Luminaire luminous efficiency 64,2 lm/W

