

BEGA**50 259**

Wall luminaire for indoor use



Project · Reference number

Date

Product data sheet

Application

LED wall luminaire · indoor luminaire made of hand-blown opal glass, satin matt and metal fitting, for all lighting tasks.

They are ideal for places where a soft and uniform lighting distribution is required.

Product description

Metal housing, finish
white enamel

Hand-blown opal glass, satin matt

2 mounting holes \varnothing 6 mm

Distance apart 280 mm

2 cable entries for through-wiring for mains

cable up to \varnothing 10.5 mm max. 3 x 1.5[□]

Connecting terminals 2.5[□]

Earth conductor connection

LED-Module for mains voltage

220-230 V \sim 50/60 Hz

Safety class I

– Safety mark

CE – Conformity mark

Weight: 3.8 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamp

Luminaire connected wattage 36 W

Rated temperature $t_a = 25$ °C

Service life criteria 50 000 h/L₇₀

50 259 K3

Module designation 3x LED-0607/830

Colour temperature 3000 K

Colour rendering index $R_a > 80$

Module luminous flux 3240 lm

Luminaire luminous flux 2224 lm

Luminaire luminous efficiency 61,8 lm/W

