

BEGA**50 354.4**

Pendant luminaire for indoor use

Project · Reference number

Date

Product data sheet

Application

Pendant luminaire · indoor luminaire with hand-blown opal glass and metal housing for non-glare light deflected downwards.

Product description

LED pendant luminaire »STUDIO LINE«
 Aluminium luminaire housing,
 velvet white enamel finish,
 Inside hue matt brass
 Hand-blown opal glass, with screw neck
 White flex suspension 2×0.5 [□]
 Overall length of luminaire approx. 1500 mm
 Connecting terminals 2.5 [□]
 Earth conductor connection
 LED power supply unit inside canopy
 220-240 V \sim 0/50-60 Hz
 Safety class I
CE – Conformity mark
 Weight: 2.4 kg

Inrush current

Inrush current: 27 A / 250 μ s
 Maximum number of luminaires of this type per miniature circuit breaker:
 B 10A: 17 luminaires
 B 16A: 27 luminaires
 C 10A: 28 luminaires
 C 16A: 45 luminaires

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamp

Module connected wattage	8.7 W
Luminaire connected wattage	11.2 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a \max} = 50$ °C


50 354.4 K3

Module designation	LED-0505/930
Colour temperature	3000 K
Colour rendering index	CRI > 90
Module luminous flux	1370 lm
Luminaire luminous flux	390 lm
Luminaire luminous efficiency	34,8 lm/W

Service life of the LED

Ambient temperature $t_a = 25$ °C
 – at > 500,000h: L 70 B 50

max. ambient temperature $t_a = 50$ °C
 – at 212,000h: L 70 B 50

**Article No. 50 354.4**

Interior colour options

- matt aluminium
- matt brass
- matt copper

Code number **.2**Code number **.4**Code number **.6**