

**BEGA****50 480.1**

Ceiling luminaire · downlight for indoor use



Project · Reference number


Date

## Product data sheet

**Application**

LED ceiling luminaire downlight · indoor luminaire with symmetrical narrow beam light distribution. Highly efficient and low-loss light distribution by means of BEGA Hybrid Optics® with reflector and optical lens.

**Product description**


Ceiling luminaire downlight »GENIUS«  
Die-cast aluminium housing,  
Velvet white enamel finish  
Trim ring · Chrome finish  
Clear safety glass  
Optical silicone lens  
Reflector surface made of pure aluminium  
2 mounting holes  $\varnothing$  4.5 mm  
Distance apart 96 mm  
Connecting terminals 2.5<sup>□</sup>  
Earth conductor connection  
LED power supply unit  
220-240 V  $\sim$  0/50-60 Hz  
DC 176-280 V  
DALI controllable  
A basic isolation exists between power cable and control line  
Safety class I  
Impact strength IK07  
Protection against mechanical impacts < 2 joule  
 – Safety mark  
**CE** – Conformity mark  
Weight: 0.95 kg

**Inrush current**

Inrush current: 5 A / 50  $\mu$ s  
Maximum number of luminaires of this type per miniature circuit breaker:  
B 10A: 31 luminaires  
B 16A: 50 luminaires  
C 10A: 52 luminaires  
C 16A: 85 luminaires

**Lamp**

Module connected wattage	8.1 W
Luminaire connected wattage	9.8 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a \max} = 35$ °C

**50 480.1 K3**

Module designation	LED-0800/930
Colour temperature	3000 K
Colour rendering index	CRI > 90
Module luminous flux	1255 lm
Luminaire luminous flux	1030 lm
Luminaire luminous efficiency	105,1 lm/W

**50 480.1 K4**

Module designation	LED-0800/940
Colour temperature	4000 K
Colour rendering index	CRI > 90
Module luminous flux	1275 lm
Luminaire luminous flux	1046 lm
Luminaire luminous efficiency	106,7 lm/W

**Service life of the LED**

Ambient temperature  $t_a = 25$  °C  
– at 400,000h: L70B50  
max. ambient temperature  $t_a = 35$  °C  
– at 360,000h: L70B50

**Lighting technology**

Symmetrical narrow beam light distribution.  
Half beam angle 21°  
Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting, as well as luminaire data in EULUMDAT and IES format are available on the BEGA website at [www.bega.com](http://www.bega.com).

**Article No. 50 480.1**

LED colour temperature optionally 3000 K or 4000 K  
3000 K – Article number + **K3**  
4000 K – Article number + **K4**

## Optional finishes

- Velvet white enamel finish Code number **.1**
- Velvet black enamel finish Code number **.5**