BEGA 55 008

Plug & Play Garden luminaire



Project · Reference number

Date

Product data sheet

Application

BEGA Plug & Play

Portable LED garden luminaire with earthspike, connecting cable and 48 V plug.

Luminaire with opal glass for a soft and uniform light distribution.

Product description

Luminaire with earthspike made of glass-fibre reinforced polyamide synthetic

Opal glass with screw neck

Silicone gasket

5 m mains supply cable with 48 V plug

Safety class III 🕸

Protection class IP 65

Dust-tight and protection against water jets

Impact strength IK06

Protection against mechanical

impacts < 1 joule

C € – Conformity mark

Weight: 1.0 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamp

Module connected wattage	1.9 W
Luminaire connected wattage	2.4 W
Rated temperature	t _a =25 °C
Ambient temperature	t _{a max} =60 °C
Voltage	48 V = DC

55 008 K3


Module designation	LED-0684/830
Colour temperature	3000 K
Colour rendering index	CRI > 80
Module luminous flux	290 lm
Luminaire luminous flux	186 lm
Luminaire luminous efficiency	77,5 lm/W

Service life of the LED

Ambient temperature t_a = 25 °C – at > 500,000 h: L70 B50

max. ambient temperature t_a = 60 °C – at 89,000 h: L70 B 50





Accessories

13566 Smart Tower with connecting cable

and mains plug

13567 Smart Tower with connecting cable

and free cable end

13568 Smart Extender

Distributor with 5 m cable and 48V plug, switchable and dimmable via Zigbee Conrol module

10596 Extension cable 5 m

10597 Extension cable 10 m

10 526 Remote control ONE

13569 Remote control PRO

70 588 Gateway

for controlling your lighting system by app BEGA Gateway from a smartphone or tablet

For the accessories a separate instructions for use can be provided upon request.

Light distribution

