

BEGA**56 342.1**

Pendant luminaire for indoor use



Project · Reference number



Date

Product data sheet

Application

Pendant luminaire · indoor luminaire for free-radiating and uniform light with hand-blown opal glass, satin matt and metal housing.

Product description

Glass support and canopy
white enamel
Hand-blown opal glass, satin matt
White flex suspension $3 \times 0,75$ □
with 1 steel messenger wire
Overall length of luminaire ~2050 mm
Connecting terminals
and earth conductor terminal 2,5 □
Lampholder GX 24 q-3/4
Electronic ballast (EEL=A2)
220-240 V \sphericalangle 0/50-60 Hz
DC 176-280 V
DC Start ≥ 198 V
Safety class I
 – Safety mark
 – Conformity mark
Weight: 2.1 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamp

Compact fluorescent lamp
TC-TELI 26 · 32 · 42 W · GX 24 q-3/4

Osram:

Dulux T/E Plus 26 W /...	1800 lm
Dulux T/E Plus 32 W /...	2400 lm
Dulux T/E Plus 42 W /...	3200 lm

Philips:

PL-T 26 W/4p	1800 lm
PL-T 32 W/4p	2400 lm
PL-T 42 W/4p	3200 lm

Please note the lamp manufacturers' operating instructions.

Article No. 56 342.1

Optional finishes

- White enamel with code number **.1**
- Chrome with code number **.3**

