

BEGA**56 599.4**

Pendant luminaire for indoor use



Project · Reference number


Date

Product data sheet

Application

Pendant luminaire for indoor use.
For freeradiating and uniform light made of hand-blown opal glass, satin matt.
Metal luminaire housing and rod.

Product description

Metal luminaire housing, rod suspension and canopy, finish brass
Hand-blown opal glass, satin matt
Diameter of rod 13 mm
Overall length of luminaire approx. 1850 mm
Connection terminal 2.5²
Earth conductor connection
2-pole connecting terminal for digital control
LED power supply unit inside canopy
220-240 V ~ 0/50-60 Hz
DALI controllable
A basic isolation exists between power cable and control line
Safety class I
 – Safety mark
 – Conformity mark
Weight: 3.4 kg

Inrush current

Inrush current: 5 A / 50 μs
Maximum number of luminaires of this type per miniature circuit breaker:
B 10A: 31 luminaires
B 16A: 50 luminaires
C 10A: 52 luminaires
C 16A: 85 luminaires

Lamp


Module connected wattage 17.1 W
Luminaire connected wattage 20 W
Rated temperature $t_a = 25\text{ °C}$
Ambient temperature $t_{a,max} = 35\text{ °C}$

56 599.4 K3

Module designation LED-0522/930
Colour temperature 3000 K
Colour rendering index CRI > 90
Module luminous flux 2400 lm
Luminaire luminous flux 1607 lm
Luminaire luminous efficiency 80,4 lm/W

56 599.4 K4

Module designation LED-0522/940
Colour temperature 4000 K
Colour rendering index CRI > 90
Module luminous flux 2440 lm
Luminaire luminous flux 1633 lm
Luminaire luminous efficiency 81,6 lm/W

**Service life of the LED**

Ambient temperature $t_a = 25\text{ °C}$
– at 200,000h: L70B50
max. ambient temperature $t_a = 35\text{ °C}$
– at 170,000h: L70B50

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Article No. 56 599.4

LED colour temperature optionally 3000 K or 4000 K
3000 K – Article number + **K3**
4000 K – Article number + **K4**

Optional finishes

- White enamel code number **.1**
- Stainless steel code number **.2**
- Chrome code number **.3**
- Brass code number **.4**

If the article number is followed by a **P**, we can also supply these luminaires in impact-resistant synthetic material.