

BEGA**66 965**

Lichtbaustein ®



Project · Reference number

Date

Product data sheet

Application

Lichtbaustein® Rectangle
Wall luminaire for corner mounting.
The luminaire is ideal for places where a soft
and uniform lighting distribution is required.
For interior and exterior applications.

Product description

Luminaire made of aluminium alloy
and stainless steel
BEGA Unidure® coating technology
Opal glass satin matt
2 mounting holes \varnothing 6 mm
Distance apart 200 mm
1 cable entry for mains supply cable
up to \varnothing 10,5 mm max. $3 \times 1,5^{\square}$
Connection terminal 2.5^{\square}
Earth conductor connection
Lampholder E 27
Safety class I
Protection class IP 44
Protected against granular foreign bodies
> 1 mm and splash water
Impact strength IK03
Protection against mechanical
impacts < 0.35 joule
 – Safety mark
CE – Conformity mark
Weight: 1.9 kg

Lamps

Luminaire with lampholder E 27
Lamp output max. 2×60 W

For this luminaire we recommend the following
BEGA LED lamps:



13510 LED 7 W · 805 lm · 2700 K

13548 LED 7 W · 805 lm · 2700 K
dimmmable

13584 LED 7 W · 805 lm · 3000 K

13586 LED 7 W · 805 lm · 3000 K
dimmmable

Detailed technical and lighting data for the
lamps can be found in the data sheets on our
website.



Light technique

Luminaire data for the light planning program
DIALux for outdoor lighting, street lighting and
indoor lighting as well as luminaire data in
EULUMDAT- and IES-format you will find on the
BEGA web page www.bega.com.

Light distribution

