

**BEGA****67 547.3**

Table lamp for indoor use

Project · Reference number

Date

**Product data sheet****Application**

Table lamp · indoor luminaire made of metal base and hand-blown opal glass for free radiating and glare-free light.

**Product description**

Luminaire made of aluminium, polished surface finish  
 Hand-blown opal glass, with screw neck  
 Built-in toggle switch  
 Black cable · 2000 mm  
 LED power supply unit  
 220-240 V ~ 50/60 Hz  
 Safety class I  
**CE** – Conformity mark  
 Weight: 2.1 kg

**Lamp**

Module connected wattage	13,4 W
Luminaire connected wattage	15 W
Rated temperature	$t_a = 25 \text{ }^\circ\text{C}$
Service life criteria	50 000 h/L <sub>70</sub>

**67 547.3**

Colour temperature	3000 K
Colour rendering index	$R_a > 85$
Module luminous flux	960 lm
Luminaire luminous flux*	800 lm
Luminaire luminous efficiency*	53,3 lm/W

**67 547.3 K4**

Colour temperature	4000 K
Colour rendering index	$R_a > 85$
Module luminous flux	1055 lm
Luminaire luminous flux*	880 lm
Luminaire luminous efficiency*	58,7 lm/W

\* preliminary data

**Article No. 67 547.3**

LED colour temperature optionally 3000 K or 4000 K  
 3000 K – Article number  
 4000 K – Article number + **K4**

