


BEGA**84 064**

Light building element



Project · Reference number

Date



Product data sheet

Product description

The luminaire consists of aluminium profiles, cast aluminium and stainless steel
 Clear safety glass
 Silicone gasket
 Reflector made of pure anodised aluminium
 Pole made of aluminium
 2 opposing cable entry points 150 × 50 mm
 Screw-on ground plate approx. 250 × 250 mm
 With inserted door made of aluminium
 Square door latch (wrench size 8 mm)
 Connection box 71 084
 for through-wiring – for 2 cables up to 7 × 6²
 Terminal connection L1 · L2 · L3 · N · PE
 2 connecting terminals for connecting DALI control cables
 Fuse terminal with micro fuse
 6,3 A slow ϕ 5 × 20 mm
 LED power supply unit
 220-240 V \sim 0/50-60 Hz
 DC 176-264 V
 During DC operation the LED power is reduced to 50 %
 DALI controllable
 A basic isolation exists between power cable and control line
 Safety class I
 Protection class IP 65
 Dust-tight and protection against water jets
 Impact strength IK06
 Protection against mechanical impacts < 1 joule
 – Safety mark
 – Conformity mark
 Wind catching area: 0.84 m²
 Weight: 43.0 kg

Application

LED light building element with rotationally symmetrical light distribution for lighting and designing squares, access roads and entrance areas.

Light building elements are luminaires which can divide and structure areas in exterior application. They have a orientating, directing and demarcating function.

Lamp

Module connected wattage 39 W
 Luminaire connected wattage 43.5 W
 Rated temperature $t_a = 25$ °C
 Ambient temperature $t_{a,max} = 25$ °C

84 064 K4

Module designation LED-0808/840
 Colour temperature 4000 K
 Colour rendering index CRI > 80
 Module luminous flux 7630 lm
 Luminaire luminous flux 2416 lm
 Luminaire luminous efficiency 55,5 lm/W

84 064 K3

Module designation LED-0808/830
 Colour temperature 3000 K
 Colour rendering index CRI > 80
 Module luminous flux 7420 lm
 Luminaire luminous flux 2349 lm
 Luminaire luminous efficiency 54 lm/W

Service life of the LED

max. ambient temperature $t_a = 25$ °C
 – at 156,000h: L70B50

Ambient temperature $t_{a,max} = 50$ °C (55 %)
 LED psu: 50,000h
 LED module: 50,000h

BEGA Thermal Control® protects temperature-sensitive luminaire components by temporarily limiting the nominal power at high temperatures.

Inrush current

Inrush current: 5 A / 100 μ s
 Maximum number of luminaires of this type per miniature circuit breaker:
 B 10A: 27 luminaires
 B 16A: 44 luminaires
 C 10A: 27 luminaires
 C 16A: 44 luminaires

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Article No. 84 064

LED colour temperature optionally 4000 K or 3000 K
 4000 K – Article number + **K4**
 3000 K – Article number + **K3**
 Colour graphite or silver
 graphite – article number
 silver – article number + **A**

Light distribution