

BEGA**84 391**

Floodlight RGBW

IP 65

Project · Reference number

Date

Product data sheet**Application**

LED floodlight with wide beam light distribution for additive colour mixing RGBW. The luminaire can be controlled by DALI colour light control (DT8, RGBWAF, xy). We recommend our BEGA Control system for this purpose. Floodlight with mounting box for permanent installation on a wall, under a ceiling or on a pillar.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
 Safety glass with optical structure
 Silicone gasket
 Reflector made of pure anodised aluminium
 Rotation range of floodlight 350°
 Swivel range -35°/+90°
 Mounting box with 2 fixing holes
 ø 4.5 mm · 67 mm spacing
 2 cable entries for through-wiring of mains supply cable ø 7-10.5 mm, max. 5G1.5[□]
 Connecting terminal 2.5[□]
 with plug connection
 Earth conductor connection
 LED power supply unit
 DALI controllable
 220-240 V ~ 50-60 Hz
 Safety class I
 Protection class IP 65
 Dust-tight and protection against water jets
 Impact strength IK08
 Protection against mechanical impacts < 5 joule
 CE – Conformity mark
 Wind catching area: 0.039 m²
 Weight: 2.8 kg


Inrush current

Inrush current: 24 A / 275 µs
 Maximum number of luminaires of this type per miniature circuit breaker:
 B10A: 11 luminaires
 B16A: 18 luminaires
 C10A: 19 luminaires
 C16A: 31 luminaires

Lamp

Module connected wattage	29 W
Luminaire connected wattage	35 W
Rated temperature	t _a = 25 °C
Ambient temperature	t _{a max} = 25 °C

Module designation	LED-0347/RGBW
Luminaire luminous flux	1761 lm
Luminaire luminous efficiency	50,3 lm/W

**Service life of the LED**

max. ambient temperature t_a = 25 °C
 – at 95,000h: L70B50

Light technique

Broad spread light distribution.
 Half beam angle 89/96°
 Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting, as well as luminaire data in EULUMDAT and IES format are available on the BEGA website at www.bega.com.

Article No. 84 391

Colour optionally graphite, white or silver
 Graphite – Article number
 White – Article number + **W**
 Silver – Article number + **A**

Accessories

70 502 Shield
 The attachable shield screens the light upwards or downwards.

A separate instructions for use can be provided upon request.