

BEGA**84 392**

Floodlight RGBW

IP 65

Project · Reference number

Date

Product data sheet

Application

LED floodlight with wide beam light distribution for additive colour mixing RGBW. The luminaire can be controlled by DALI colour light control (DT8, RGBWAF, xy). We recommend our BEGA Control system for this purpose. Floodlight with mounting box for permanent installation on a wall, under a ceiling or on a pillar.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
 Safety glass with optical structure
 Reflector made of pure anodised aluminium
 Rotation range of floodlight 350°
 Swivel range -35°/+70°
 Mounting box with 2 fixing holes
 ø 4.5 mm · 67 mm spacing
 2 cable entries for through-wiring of mains supply cable ø 7-10,5 mm, max. 5 G 1.5[□]
 Connecting terminal 2.5[□] with plug connection
 Earth conductor connection
 LED power supply unit
 DALI controllable
 220-240 V ~ 0/50-60 Hz
 Safety class I
 Protection class IP 65
 Dust-tight and protection against water jets
 Impact strength IK07
 Protection against mechanical impacts < 2 joule
 CE – Conformity mark
 Wind catching area: 0.04 m²
 Weight: 4.1 kg


Light technique

Broad spread light distribution.
 Half beam angle 81/83°
 Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and interior lighting as well as luminaire data in EULUMDAT and IES format are available on the BEGA website www.bega.com.

Lamp

Module connected wattage	58 W
Luminaire connected wattage	66 W
Rated temperature	$t_a = 25 \text{ °C}$
Ambient temperature	$t_{a \text{ max}} = 35 \text{ °C}$

Module designation	LED-0555/RGBW
Luminaire luminous flux	3586 lm
Luminaire luminous efficiency	54,3 lm/W

**Lifetime of the LED**

Ambient temperature $t_a = 15 \text{ °C}$
 – at 50,000 h: L80B10
 – at 95,000 h: L70B50

Ambient temperature $t_a = 25 \text{ °C}$
 – at 50,000 h: L70B10
 – at 65,000 h: L70B50

max. ambient temperature $t_a = 35 \text{ °C}$
 – at 50,000 h: L70B50
 – at 50,000 h: L70B50

Article No. 84 392

Colour optionally graphite, white or silver
 Graphite – Article number
 White – Article number + **W**
 Silver – Article number + **A**

Accessories**70 525 Shield**

The attachable shield screens the light upwards or downwards.

A separate instructions for use can be provided upon request.