

Titan Semi-Recessed

Type	Downlight
Mounting	Semi-recessed
Material	Aluminium
Adjustable	Yes (40°/359°)
El. class / IP	Class III / IP20
El. class driver	Class II
Warranty:	see p.308


Bridgelux Vero 10 LED (350mA)

CCT	2700K / 3000K / 4000K
CRI	Ra90 (Ra80 on request)
SDCM	3
Luminous Flux LED	2700K - Ra90: 1100lm (124lm/W) 3000K - Ra90: 1156lm (130lm/W) 4000K - Ra90: 1172lm (132lm/W)
Luminous Flux System	2700K - Ra90: 937lm (92lm/W) 3000K - Ra90: 984lm (96lm/W) 4000K - Ra90: 998lm (98lm/W)
Beam angle	28° / 40°
LED Power	8.9W / 350mA (excl. driver)
System Power	10.2W / 350mA (incl. driver)
Forward voltage	23V (min.) - 25.5V (typ.) - 28V (max.)

Bridgelux Dim-to-warm LED (250mA)

CCT	Dim-to-warm 1800-3000K
CRI	Ra90
Luminous Flux LED	LED: 860lm - System: 732lm
LED Power	8.2W / 250mA (excl. driver)
System Power	9.4W / 250mA (incl. driver)

DIM TO WARM




Weight: 425g
(excl. driver)



Driver:
- Included in article number and included in price
- External/Remote installation
Data sheets and wiring guide: see website
Driver information: see p.294-295

On Request
Bridgelux Vero10 CRI Ra97





Titan Semi-Recessed

Cone

PRICES INCL. DRIVERS

Non dim (Driver 490.24.16 incl.)

2700K - Ra90 - 10.2W - 937lm	1200. AA.24.927.XX
3000K - Ra90 - 10.2W - 984lm	1200. AA.24.930.XX
4000K - Ra90 - 10.2W - 998lm	1200. AA.24.940.XX

1-10V dim & Push dim (Driver 490.25.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1200. AA.25.927.XX
3000K - Ra90 - 10.2W - 984lm	1200. AA.25.930.XX
4000K - Ra90 - 10.2W - 998lm	1200. AA.25.940.XX

DALI dim (Driver 490.26.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1200. AA.26.927.XX
3000K - Ra90 - 10.2W - 984lm	1200. AA.26.930.XX
4000K - Ra90 - 10.2W - 998lm	1200. AA.26.940.XX

Mains dim (Driver 490.27.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1200. AA.27.927.XX
3000K - Ra90 - 10.2W - 984lm	1200. AA.27.930.XX
4000K - Ra90 - 10.2W - 998lm	1200. AA.27.940.XX

DALI dim / Dim to Warm 1800-3000K (Driver 490.26.20 incl.)

DTW (DALI dim) - 9.4W - 732lm	1200. AA.26.dtw.XX
-------------------------------	------------------------------------

Mains dim / Dim to Warm 1800-3000K (Driver 497.27.20 incl.)

DTW (mains dim) - 9.4W - 732lm	1200. AA.27.dtw.XX
--------------------------------	------------------------------------



Titan Semi-Recessed

Organic

PRICES INCL. DRIVERS

Non dim (Driver 490.24.16 incl.)

2700K - Ra90 - 10.2W - 937lm	1201. AA.24.927.XX
3000K - Ra90 - 10.2W - 984lm	1201. AA.24.930.XX
4000K - Ra90 - 10.2W - 998lm	1201. AA.24.940.XX

1-10V dim & Push dim (Driver 490.25.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1201. AA.25.927.XX
3000K - Ra90 - 10.2W - 984lm	1201. AA.25.930.XX
4000K - Ra90 - 10.2W - 998lm	1201. AA.25.940.XX

DALI dim (Driver 490.26.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1201. AA.26.927.XX
3000K - Ra90 - 10.2W - 984lm	1201. AA.26.930.XX
4000K - Ra90 - 10.2W - 998lm	1201. AA.26.940.XX

Mains dim (Driver 490.27.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1201. AA.27.927.XX
3000K - Ra90 - 10.2W - 984lm	1201. AA.27.930.XX
4000K - Ra90 - 10.2W - 998lm	1201. AA.27.940.XX

DALI dim / Dim to Warm 1800-3000K (Driver 490.26.20 incl.)

DTW (DALI dim) - 9.4W - 732lm	1201. AA.26.dtw.XX
-------------------------------	------------------------------------

Mains dim / Dim to Warm 1800-3000K (Driver 497.27.20 incl.)

DTW (mains dim) - 9.4W - 732lm	1201. AA.27.dtw.XX
--------------------------------	------------------------------------



Titan Semi-Recessed

Anti-glare

PRICES INCL. DRIVERS

Non dim (Driver 490.24.16 incl.)

2700K - Ra90 - 10.2W - 937lm	1202. AA.24.927.XX
3000K - Ra90 - 10.2W - 984lm	1202. AA.24.930.XX
4000K - Ra90 - 10.2W - 998lm	1202. AA.24.940.XX

1-10V dim & Push dim (Driver 490.25.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1202. AA.25.927.XX
3000K - Ra90 - 10.2W - 984lm	1202. AA.25.930.XX
4000K - Ra90 - 10.2W - 998lm	1202. AA.25.940.XX

DALI dim (Driver 490.26.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1202. AA.26.927.XX
3000K - Ra90 - 10.2W - 984lm	1202. AA.26.930.XX
4000K - Ra90 - 10.2W - 998lm	1202. AA.26.940.XX

Mains dim (Driver 490.27.20 incl.)

2700K - Ra90 - 10.2W - 937lm	1202. AA.27.927.XX
3000K - Ra90 - 10.2W - 984lm	1202. AA.27.930.XX
4000K - Ra90 - 10.2W - 998lm	1202. AA.27.940.XX

DALI dim / Dim to Warm 1800-3000K (Driver 490.26.20 incl.)

DTW (DALI dim) - 9.4W - 732lm	1202. AA.26.dtw.XX
-------------------------------	------------------------------------

Mains dim / Dim to Warm 1800-3000K (Driver 497.27.20 incl.)

DTW (mains dim) - 9.4W - 732lm	1202. AA.27.dtw.XX
--------------------------------	------------------------------------

28° Reflector: 0000.[28.00.000.00](#)
40° Reflector: 0000.[40.00.000.00](#)

Available colors: 0000.00.00.00.[XX](#)
Other RAL colors on request

01



White Matt Text.
Standard

18



Grey Matt Text.
Standard

03



Black Matt Text.
Standard

25



Smoked Brown Text. Black + Gold Matt
Standard

11



16



Gold Matt