

Cricket

D60 F17 27

Bridgewell Consulting LTD

Anodized aluminium structure.

tipology



suggested bulb and options (n.i.)

A10401C10

GU4

1x20W

HRGS

38°

η 89,20%



volume – weight

0,003 m³ – 0,35 Kg

technical information



IP67

150° C



TEMPERED GLASS

accessories included

notes

For wall/floor

accessories not included

A22101 Electronic transformer 60W 230/12V (min 10W-max 60W) (max 3 spots)

A22102 Electronic transformer 100W 230/12V (min 35W-max 100W)
(min 2 – max 5 spots)

A22201 Electronic transformer 150W 230/12V (min 75W-max 150W)
(min 4 – max 7 spots)




A22202 Electronic transformer 200W 230/12V (min 100W-max 200W)
(min 5 – max 10 spots)

A22001 Toroidal transformer 20W 230/12V (max 1 spot)

A22002 Toroidal transformer 230/12V 50W IP67 (max 2 spot)





D60Z07 Ceiling-wall housing

See next page





Cricket D60 Moduli per controsoffitto *Modules for false ceiling*

Codice Code	Descrizione Description	Cassaforma Wallbox	Disegno tecnico quotato Quoted technical drawing
D60 F15 F16 F19 F20		D60 Z05 Cassaforma per pavimento <i>Floor housing</i>	
D60 F13 F15 F16 F17 F19 F20		D60 Z07 Anello per cartongesso <i>False ceiling ring</i>	
D60 F27 F28		D60 Z09 Cassaforma per pavimento <i>Floor housing</i>	
D60 F25 F27 F28		D60 Z11 Anello per cartongesso <i>False ceiling ring</i>	
D60 F15 F16 F19 F20		D60 Z13 Cassaforma per pavimento <i>Floor housing</i>	