

THE BLACK LINE TRIM 4 SPOTS

Number of heads

Mounting Ceiling recessed

Lamps descriptionPower LED 13W 4 x 200 lm 3000K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

OPTICAL

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 42° Flood

ELECTRICAL

Transformer availability
Separate item
Transformer mounting
Remote
Transformer type
Electronic
Emergency
Insulation class
Class III

PHYSICAL

Length (mm) 391 Recessed depth (mm) 101

Construction material Extruded aluminum

Weight (kg) 1,47






The Black Line Trim 4 Spots designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. 1050 mA remote power supply not included.

03.0056.00A - 713lm Primer 03.0056.40A - 713lm White



CERTIFICATIONS











Flos.architectural@flos.com www.flos.com



The Black Line Trim 4 Spots . Accessories

Power Supply







60.8530

Constant Current Power Supply for LED. 25-50W

Continuous current power supply of 25-50W, 220/240V - 50/60Hz with power current selected through adjustable 350/500/550/650/700/750/850/900/1050mA Dali switch, I-10V switch or push dimming.

Maximum lenght of 1.5 mm2 secundary conductor (m): 10

Maximum lenght of 2.5 mm2 secundary conductor (m): 15

60.8548

Constant Current Power Supply for LED. 24/33W

Continuous current power supply of 24/33W, 220/240V - 50/60Hz with power current selected through adjustable 500/1050 mA.

Maximum lenght of 1.5 mm2 secundary conductor (m): 20

Maximum lenght of 2.5 mm2 secundary conductor (m): 30

60.9276

Continuous current power supply of 20-40W

Continuous current power supply of 20-40W, 110/240V - 50/60Hz with power current selected through adjustable 350/400/500/550/600/650/700/750/-800/850/900/950 mA Dali switch, 1-10V switch or push dimming.

Maximum lenght of 1.5 mm2 secundary conductor (m): 10


Maximum lenght of 2.5 mm2 secundary conductor (m): 15



The Black Line Trim 4 Spots designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. 1050 mA remote power supply not included.

03.0056.00A - 713lm Primer 03.0056.40A - 713lm White



The Black Line Trim 4 Spots . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED

CERTIFICATIONS













Flos.architectural@flos.com www.flos.com