

### THE BLACK LINE NO TRIM 4 SPOTS

Number of heads

**Mounting** Ceiling recessed

Lamps descriptionPower LED 13W 4 x 200 lm 3000K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

**Environment** Indoor

**Notes** No Trim version can be connected in a continuous line.

### **OPTICAL**

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 42° Flood

### **ELECTRICAL**

Transformer availability
Separate item
Transformer mounting
Remote
Transformer type
Electronic
Emergency
Insulation class
Class III

### **PHYSICAL**

Length (mm) 350 Recessed depth (mm) 71

Construction material Extruded aluminum

Weight (kg) 1,27






The Black Line No Trim 4 Spots designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. 1050 mA remote power supply not included.

03.0056.14.ANT - 713lm Black



350

### CERTIFICATIONS













Flos.architectural@flos.com www.flos.com



### The Black Line No Trim 4 Spots . Accessories

### **Power Supply**









60.8530

## Constant Current Power Supply for LED. 25-50W

Continuous current power supply of 25-50W, 220/240V - 50/60Hz with power current selected through adjustable 350/500/550/650/700/750/850/900/1050mA Dali switch, I-10V switch or push dimming.

Maximum lenght of 1.5 mm2 secundary conductor (m): 10

Maximum lenght of 2.5 mm2 secundary conductor (m): 15

60.8548

## Constant Current Power Supply for LED. 24/33W

Continuous current power supply of 24/33W, 220/240V - 50/60Hz with power current selected through adjustable 500/1050 mA.

Maximum lenght of 1.5 mm2 secundary conductor (m): 20

Maximum lenght of 2.5 mm2 secundary conductor (m): 30

60.9276

# Continuous current power supply of 20-40W

Continuous current power supply of 20-40W, 110/240V - 50/60Hz with power current selected through adjustable 350/400/500/550/600/650/700/750/-800/850/900/950 mA Dali switch, 1-10V switch or push dimming.

Maximum lenght of 1.5 mm2 secundary conductor (m): 10

Maximum lenght of 2.5 mm2 secundary conductor (m): 15




# The Black Line No Trim 4 Spots designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. 1050 mA remote power supply not included.



03.0056.14.ANT - 713lm Black



350

### The Black Line No Trim 4 Spots . Lamps



**Power LED** 

Lamp category:

**LED** 

Socket:

Special base

Lamp type:

Power LED

### **CERTIFICATIONS**











Flos.architectural@flos.com www.flos.com