

THE BLACK LINE TRIM 12 SPOTS

Number of heads	1
Mounting	Ceiling recessed
Lamps description	Power LED 39W 12 x 200 lm 3000K CRI 90
Luminaire luminous flux	Extreme Cut-off. See reference number
Environment	Indoor

OPTICAL


Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	11° Spot

ELECTRICAL

Transformer availability	Separate item
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class III

PHYSICAL


Length (mm)	1031
Recessed depth (mm)	101
Construction material	Extruded aluminum
Weight (kg)	3,81




The Black Line Trim 12 Spots
designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. 1050 mA remote power supply not included.

- 03.0062.00A - 2330lm Primer
- 03.0062.40A - 2330lm White



CERTIFICATIONS



The Black Line Trim 12 Spots . Accessories

Power Supply




60.8530

Constant Current Power Supply for LED. 25-50W

Continuous current power supply of 25-50W, 220/240V - 50/60Hz with power current selected through adjustable 350/500/550/650/700/750/850/900/1050mA Dali switch, 1-10V switch or push dimming.

Maximum length of 1.5 mm² secondary conductor (m): 10


Maximum length of 2.5 mm² secondary conductor (m): 15



The Black Line Trim 12 Spots designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. 1050 mA remote power supply not included.

- 03.0062.00A - 2330lm Primer
- 03.0062.40A - 2330lm White



The Black Line Trim 12 Spots . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED

CERTIFICATIONS

