

THE BLACK LINE TRIM 12 SPOTS

Number of heads

Mounting Ceiling recessed

Lamps descriptionPower LED 39W 12 x 197 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

OPTICAL

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle II° Spot

ELECTRICAL

Transformer availability

Separate item

Transformer mounting

Remote

Transformer type

Electronic

Emergency

Insulation class

Class III


PHYSICAL

Length (mm) 1031 Recessed depth (mm) 101

Construction material Extruded aluminum

Weight (kg) 3,81






The Black Line Trim 12 Spots designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. 1050 mA remote power supply not included.

03.0063.00A - 2046lm Primer 03.0063.40A - 2046lm White



CERTIFICATIONS











Flos.architectural@flos.com www.flos.com



The Black Line Trim 12 Spots . Accessories

Power Supply



60.8530

Constant Current Power Supply for LED. 25-50W

Continuous current power supply of 25-50W, 220/240V - 50/60Hz with power current selected through adjustable 350/500/550/650/700/750/850/900/1050mA Dali switch, 1-10V switch or push dimming.

Maximum lenght of 1.5 mm2 secundary conductor (m): 10

Maximum lenght of 2.5 mm2 secundary conductor (m): 15

The Black Line Trim 12 Spots . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED


Flos.architectural@flos.com



The Black Line Trim 12 Spots designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. 1050 mA remote power supply not included.

03.0063.00A - 2046lm Primer 03.0063.40A - 2046lm White



CERTIFICATIONS







GWT

850°



