### FLOS

### COMPASS BOX SMALL IL

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment

Ceiling surface LED Array 6,2W 703 Im 3000K CRI 80 See reference number 220/240 Indoor



Aiming **B**eam angle Adjustable 26° Medium

Included

Integral

Electronic

Without

Class II

Т

### ELECTRICAL

Transformer availability **Transformer mounting** Transformer type Emergency Insulation class

### PHYSICAL

Length (mm)	100
Width (mm)	100
Height (mm)	160
Construction material	Alumi
Weight (kg)	I


inium





Compass Box Small IL designed by FLOS Architectural

Surface spotlight to be installed on ceiling/wall with LED light source. Non-regulable 220-240V, 50-60Hz power supply integrated in luminaire body.







CERTIFICATIONS

**₹**{}03







Flos.architectural@flos.com

## FLOS

### **Compass Box Small IL**. Accessories

Optical





08.8196.14

Honeycomb

"Honeycomb" anti-glare grid in aluminium cells with black liquid paint finish.



Screening cylinder

Screening cylinder with rotating pin in a black thermoplastic material

### Compass Box Small IL . Lamps




LED Array Lamp category: LED Socket: Special base Lamp type: LED Array




Compass Box Small IL designed by FLOS Architectural

Surface spotlight to be installed on ceiling/wall with LED light source. Non-regulable 220-240V, 50-60Hz power supply integrated in luminaire body.







# CERTIFICATIONS