

COMPASS BOX SMALL 4L

Number of heads

Mounting Ceiling surface

Lamps description 4 x LED Array 6,2W 703 lm 3000K CRI 80

Luminaire luminous flux See reference number

Voltage (V) 220/240 Environment Indoor



OPTICAL

Aiming Adjustable

Beam angle 26° Medium

ELECTRICAL

Transformer availability Included
Transformer mounting Integral
Transformer type Electronic
Emergency Without
Insulation class Class I

PHYSICAL

Length (mm)325Width (mm)100Height (mm)160Construction materialAluminium

Weight (kg) 3



Compass Box Small 4L designed by FLOS Architectural

Surface spotlight to be installed on ceiling/wall with LED light source. Non-regulable 220-240V, 50-60Hz power supply integrated in luminaire body.

03.2641.30A - 4x584lm Matt white
03.2641.29A - 4x584lm Anodised aluminium
03.2641.14A - 4x584lm Matt black
03.2641.WGA - 4x584lm Wenge
03.2641.TKA - 4x584lm Teak





CERTIFICATIONS















Flos.architectural@flos.com www.flos.com



Compass Box Small 4L . Accessories

Optical





08.8196.14

Honeycomb

"Honeycomb" anti-glare grid in aluminium cells with black liquid paint finish.

08.8238.14

Screening cylinder

Screening cylinder with rotating pin in a black thermoplastic material

Compass Box Small 4L . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:

LED Array



Compass Box Small 4L

designed by FLOS Architectural

Surface spotlight to be installed on ceiling/wall with LED light source. Non-regulable 220-240V, 50-60Hz power supply integrated in luminaire body.

03.2641.30A - 4x584lm Matt white

03.2641.29A - 4x584lm Anodised aluminium

03.2641.14A - 4x584lm Matt black 03.2641.WGA - 4x584lm Wenge

03.2641.TKA - 4x584lm Teak

00





CERTIFICATIONS















Flos.architectural@flos.com www.flos.com