

COMPASS BOX SMALL 4L SQUARE

Number of heads 4

Mounting Ceiling surface

Lamps description 4 x LED Array 6,2W 703 lm 3000K CRI 80

Luminaire luminous flux See reference number

Voltage (V) 220/240 Environment Indoor



OPTICAL

Aiming Adjustable

Beam angle 59° Wide Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Integral
Transformer type Electronic
Emergency Without
Insulation class Class I

PHYSICAL

Length (mm)184Width (mm)175Height (mm)160Construction materialAluminiumWeight (kg)2,80



Compass Box Small 4L Square designed by FLOS Architectural

Surface spotlight to be installed on ceiling/wall with LED light source. Non-regulable 220-240V, 50-60Hz power supply integrated in luminaire body.

03.2647.30A - 4x552lm Matt white
03.2647.29A - 4x552lm Anodised aluminium
03.2647.14A - 4x552lm Matt black
03.2647.WGA - 4x552lm Wenge

03.2647.TKA - 4x552lm Teak





CERTIFICATIONS















Flos.architectural@flos.com www.flos.com



Compass Box Small 4L Square . Accessories

Optical





08.8196.14

Honeycomb

"Honeycomb" anti-glare grid in aluminium cells with black liquid paint finish.

08.8238.14

Screening cylinder

Screening cylinder with rotating pin in a black thermoplastic material

Compass Box Small 4L Square . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:

LED Array



Compass Box Small 4L Square designed by FLOS Architectural

Surface spotlight to be installed on ceiling/wall with LED light source. Non-regulable 220-240V, 50-60Hz power supply integrated in luminaire body.


03.2647.30A - 4x552lm Matt white


03.2647.29A - 4x552lm Anodised aluminium

03.2647.14A - 4x552lm Matt black

03.2647.WGA - 4x552lm Wenge

03.2647.TKA - 4x552lm Teak





CERTIFICATIONS















Flos.architectural@flos.com www.flos.com