

KAP Ø145

Number of heads	1
Mounting	Ceiling recessed
Lamps description	QT-12 GY6.35 Max 65W IRC
Voltage (V)	12
Environment	Indoor
Notes	Pre-installation frame. To be ordered separately.

OPTICAL


Light controller description	Glass diffuser
Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	56°, 61°, 62°

ELECTRICAL

Transformer availability	Separate item
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class III

PHYSICAL


Cutout diameter (mm)	165
Diameter (mm)	145
Recessed depth (mm)	165
Construction material	Die-cast aluminum
Weight (kg)	0,92



Kap Ø145
designed by FLOS Architectural

Recessed 12V halogen lamp luminaire.
Remote transformer not included.

● 03.4491.GL (56°)	Gold
● 03.4491.B1 (62°)	White
● 03.4491.BU (62°)	Blue
● 03.4491.74 (61°)	Black
● 03.4491.CU	Copper




CERTIFICATIONS



Kap Ø145 . Accessories

Mounting



08.8156.00

Installation Frame No Trim



08.8421.00

Installation can for concrete KAP Ø145



08.8491.30


08.8491.GL

08.8491.BU

08.8491.14

Installation Frame Trim



Installation frame Kap Ø145/ Kap Ø145 wall washer. Copper finish trim frame not available. Combine with withe or any of the other finishes according to the desired final aesthetic effect.



Kap Ø145
designed by FLOS Architectural

Recessed 12V halogen lamp luminaire. Remote transformer not included.

03.4491.GL (56°)	Gold
03.4491.B1 (62°)	White
03.4491.BU (62°)	Blue
03.4491.74 (61°)	Black
03.4491.CU	Copper



Kap Ø145 . Lamps



60.6404 IRC

QT-I2

Lamp Watt:
35 W

Lamp category:
Halogen low voltage

Socket:
GY6.35

Color temperature (K):
2900 °K

Catalog reference:
60.6404 IRC

Lamp type:
Flos architectural@flos.com



60.6399 IRC

QT-I2

Lamp Watt:
50 W

Lamp category:
Halogen low voltage

Socket:
GY6.35

Color temperature (K):
3000 °K

Catalog reference:
60.6399 IRC

Lamp type:
QT-I2

CERTIFICATIONS

