FLOS

LIGHT SNIPER FIXED SQUARE DALI VERSION

L

Bare lamps

Symmetric

14° Spot

Fixed

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment

Ceiling recessed Power LED 11W 1060 Im 3000K CRI 90 Extreme Cut-off. See reference number 220/240 Indoor

OPTICAL

Light controller description Aiming Light distribution symmetry Beam angle

ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

Included Remote Electronic dimmable dali Without Class II

PHYSICAL

Cutout diameter (mm) Recessed depth (mm) Construction material Weight (kg) 90 165 Aluminium 0,49







Light Sniper Fixed Square Dali Version

designed by FLOS Architectural


High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.














GWT

850°

H

Light Sniper Fixed Square Dali Version . Accessories

Optical





08.8041.68

Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.



Honeycomb

"Honeycomb" anti-glare grid made of aluminium cells.



Light Sniper Fixed Square Dali Version

designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.



Ø90

30 max

95

Mounting





08.8240.00B

Flush ceilling square frame accessory

08.8243.00


08.8243.00.5U 08.8243.00.1U

Ceiling protector accessory.




08.8250.00

Concrete instalation can.



44

100



FLOS

Light Sniper Fixed Square Dali Version . Accessories



08.8222.30A

Ceiling protector accessory. Square

Light Sniper Fixed Square Dali Version . Lamps



Power LED LED Socket: Special base Lamp type: Power LED





