# FLOS

### LIGHT SNIPER FIXED SQUARE DALI VERSION

L

Bare lamps

Symmetric

14° Spot

Fixed

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment

Ceiling recessed Power LED 11W 910 Im 2700K CRI 90 Extreme Cut-off. See reference number 220/240 Indoor

### OPTICAL

Light controller description Aiming Light distribution symmetry Beam angle

### ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

## Included Remote Electronic dimmable dali Without Class II

### PHYSICAL

Cutout diameter (mm) Recessed depth (mm) Construction material Weight (kg) 90 165 Aluminium 0,49








Light Sniper Fixed Square Dali Version

designed by FLOS Architectural


High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.








CERTIFICATIONS







## F

### Light Sniper Fixed Square Dali Version . Accessories

#### Optical





08.8041.68

**Elliptical light** distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.



Honeycomb

"Honeycomb" anti-glare grid made of aluminium cells.



Light Sniper Fixed Square Dali Version

designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.

03.4983.06.DA - 336lm	Chrome
<b>03.4983.GL.DA - 336</b> Im	Gold
03.4983.14.DA - 336lm	Matt black

Ø90

٨ 30 max

95

### Mounting





08.8240.00B

Flush ceilling square frame accessory

08.8243.00


08.8243.00.5U 08.8243.00.1U

Ceiling protector accessory.




08.8250.00

**Concrete instalation** can.





100



# FLOS

### Light Sniper Fixed Square Dali Version . Accessories



08.8222.30A

Ceiling protector accessory. Square

Light Sniper Fixed Square Dali Version . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



High-performance embedded light

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.



