## FLOS

#### LIGHT SNIPER ADJUSTABLE SQUARE

L

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment

Ceiling recessed Power LED 11W 1060 Im 3000K CRI 90 Extreme Cut-off. See reference number 220/240 Indoor

#### OPTICAL

Light controller descriptionBare lampsAimingAdjustableLight distribution symmetrySymmetricBeam angle13° Spot

#### ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

#### PHYSICAL

Cutout diameter (mm)
Recessed depth (mm)
Construction material
Weight (kg)

90 155

Aluminium

Included

Remote

Electronic

Without


Class II







Light Sniper Adjustable Square designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.







# (

#### Light Sniper Adjustable Square . Accessories

#### Optical





08.8041.68

**Elliptical light** distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.



08.8412.14

Honeycomb

"Honeycomb" anti-glare grid made of aluminium cells.



Light Sniper Adjustable Square designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.



### Ø90 30 max 106 100

Mounting





08.8240.00B

Flush ceilling square frame accessory

08.8243.00

08.8243.00.5U

08.8243.00.1U

Ceiling protector accessory.



08.8250.00

**Concrete instalation** can.

CERTIFICATIONS GWT CE ۱F **K**03 850° <u>/</u> 40° IP 

360°



44

### F

#### Light Sniper Adjustable Square . Accessories



08.8222.30A

**Ceiling protector** accessory. Square

Light Sniper Adjustable Square . Lamps




Power LED Lamp category: LED Socket: Special base Lamp type: Power LED




Light Sniper Adjustable Square designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.







360°

44