FLOS

LIGHT SNIPER FIXED ROUND DALI VERSION

L

Bare lamps

Symmetric

Included

Remote

Without

Class II

Electronic dimmable dali

28° Medium

Fixed

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment

Ceiling recessed Power LED 11W 1060 Im 3000K CRI 90 Extreme Cut-off. See reference number 220/240 Indoor

OPTICAL

Light controller description Aiming Light distribution symmetry Beam angle

ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

PHYSICAL

Cutout diameter (mm) Diameter (mm) Recessed depth (mm) Construction material Weight (kg)









designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.









(

Light Sniper Fixed Round Dali Version . Accessories

Optical





08.8041.68

Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.



Honeycomb

"Honeycomb" anti-glare grid made of aluminium cells.



Light Sniper Fixed Round Dali Version designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.



Ø90

Mounting



08.8239.00B

Flush ceilling round frame accessory

08.8243.00

08.8243.00.5U 08.8243.00.1U

Ceiling protector accessory.



08.8250.00

Concrete instalation can.

CERTIFICATIONS






30 max

104

44

\F

Ø100



FLOS

Light Sniper Fixed Round Dali Version . Accessories





08.8229.30A


Ceiling protector accessory. Round











Light Sniper Fixed Round Dali Version . Lamps



Power LED LED Socket: Special base Lamp type: Power LED