FLOS

LIGHT SNIPER FIXED SQUARE

L

Bare lamps

Symmetric

Included

Remote

Electronic

Without

Class II

26° Medium

Fixed

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment

Ceiling recessed Power LED 11W 1060 Im 3000K CRI 90 Extreme Cut-off. See reference number 220/240 Indoor

OPTICAL

Light controller description Aiming Light distribution symmetry Beam angle


ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

PHYSICAL

Cutout diameter (mm) Recessed depth (mm) Construction material Weight (kg) 90 165 Aluminium


0,49








Light Sniper Fixed Square designed by FLOS Architectural


High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.











FLOS

Light Sniper Fixed Square . Accessories

Optical





08.8041.68

Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.



Honeycomb


"Honeycomb" anti-glare grid made of aluminium cells.



Light Sniper Fixed Square designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.





Mounting



08.8240.00B

Flush ceilling square frame accessory

08.8243.00

08.8243.00.5U 08.8243.00.1U


Ceiling protector accessory.




08.8250.00

Concrete instalation can.

CERTIFICATIONS







FLOS

Light Sniper Fixed Square . Accessories



Light Sniper Fixed Square . Lamps



Power LED Lamp category: LED Socket: Special base Lamp type: Power LED



Light Sniper Fixed Square designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.

