FLOS

LIGHT SNIPER ADJUSTABLE ROUND DALI VERSION

L

Bare lamps

Adjustable

Symmetric

25° Medium

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment

Ceiling recessed Power LED 11W 1060 Im 3000K CRI 90 Extreme Cut-off. See reference number 220/240 Indoor

OPTICAL

Light controller description Aiming Light distribution symmetry Beam angle

ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

PHYSICAL

Cutout diameter (mm)	
Diameter (mm)	
Recessed depth (mm)	
Construction material	
Weight (kg)	

Included Remote Electronic dimmable dali Without Class II

90 100 155








High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.





CERTIFICATIONS

X03

360°

CE	
<u>≁</u> 40°	

GWT 850°
IP
44

(

Light Sniper Adjustable Round Dali Version . Accessories

Optical





08.8041.68

Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.



Honeycomb

"Honeycomb" anti-glare grid made of aluminium cells.



Light Sniper Adjustable Round Dali Version

designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.



Ø90

x

Ø100

Mounting



08.8239.00B

Flush ceilling round frame accessory

08.8243.00

08.8243.00.5U 08.8243.00.1U

Ceiling protector accessory.



08.8250.00

Concrete instalation can.

CERTIFICATIONS CE F **X**03

360°

 \checkmark

40°

7	GWT 850°
]	IP 44

30 max

106

FLOS

Light Sniper Adjustable Round Dali Version . Accessories



08.8229.30A

Ceiling protector accessory. Round

Light Sniper Adjustable Round Dali Version . Lamps



Power LED LED Socket: Special base Lamp type: Power LED





