

LIGHT SNIPER ADJUSTABLE SQUARE

Number of heads

Mounting Ceiling recessed

Lamps descriptionPower LED 11W 1060 lm 3000K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Voltage (V) 220/240
Environment Indoor

OPTICAL

Light controller descriptionBare lampsAimingAdjustableLight distribution symmetrySymmetricBeam angle25° Medium

ELECTRICAL

Transformer availability Included
Transformer mounting Remote
Transformer type Electronic
Emergency Without
Insulation class Class II

PHYSICAL

Cutout diameter (mm)90Recessed depth (mm)155Construction materialAluminiumWeight (kg)0,65






Light Sniper Adjustable Square designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.

03.4998.06A - 667lm Chrome
03.4998.GLA - 667lm Gold
03.4998.14A - 667lm Matt black



CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com



Light Sniper Adjustable Square. Accessories

Optical





08.8041.68

Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.

08.8412.14

Honeycomb

"Honeycomb" anti-glare grid made of aluminium cells.



Light Sniper Adjustable Square designed by FLOS Architectural


High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.

03.4998.06A - 667lm Chrome 03.4998.GLA - 667lm Gold 03.4998.14A - 667lm Matt black

Mounting







08.8240.00B

Flush ceilling square frame accessory

08.8243.00

08.8243.00.5U

08.8243.00.1U

Ceiling protector accessory.

08.8250.00

Concrete instalation can.

CERTIFICATIONS







GWT 850°







ΙP 44

Flos.architectural@flos.com www.flos.com



Light Sniper Adjustable Square . Accessories



08.8222.30A

Ceiling protector accessory. Square

Light Sniper Adjustable Square . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:


Power LED



Light Sniper Adjustable Square designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.

03.4998.06A - 667lm Chrome
03.4998.GLA - 667lm Gold
03.4998.14A - 667lm Matt black



CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com