

KAP SUSPENSION Ø100

Number of heads

Mounting Pendant

Lamps descriptionPower LED 9W 850 Im 3000K CRI 80Luminaire luminous fluxExtreme Cut-off. See reference number

1

Voltage (V) 220/240
Environment Indoor

OPTICAL

Reflector finish Gold
Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 33°

ELECTRICAL

Number of ballast

Transformer availability Included
Transformer mounting Integral
Transformer type Electronic
Emergency Without
Insulation class Class I

PHYSICAL

Diameter (mm) 100

Construction material Extruded aluminum

Weight (kg) 1,10






Kap Suspension Ø100 designed by FLOS Architectural

Hanging luminaire for mounting in ceiling with led light source. non-regulable 220- 240V, 50/60hz power supply integrated in luminaire body.

03.5811.11A - 359lm White / Matt Gold
03.5811.ASA - 359lm Brushed Aluminium / Matt Gold
03.5811.ANA - 359lm Black / Matt Gold
03.5811.B3A - 359lm Brown / Matt Gold



CERTIFICATIONS











IP 20

Flos.architectural@flos.com www.flos.com



Kap Suspension Ø100. Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:


Power LED



Kap Suspension Ø100 designed by FLOS Architectural

Hanging luminaire for mounting in ceiling with led light source. non-regulable 220- 240V, 50/60hz power supply integrated in luminaire body.

03.5811.11A - 359lm White / Matt Gold
03.5811.ASA - 359lm Brushed Aluminium / Matt Gold
03.5811.ANA - 359lm Black / Matt Gold
03.5811.B3A - 359lm Brown / Matt Gold



CERTIFICATIONS







GWT

850°



Flos.architectural@flos.com www.flos.com