FLOS

LIGHT SHOOTER FIXED NO TRIM

Number of heads	1
Mounting	Ceiling recessed
Lamps description	Power LED 10W 850 lm 2700K CRI 90
Luminaire luminous flux	Extreme Cut-off. See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	LED: All the models include an accessory for IP54. Pre- installation frame included in No Trim versions.

OPTICAL

AimingFixedLight distribution symmetrySymmetricBeam angle12° Spot

ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

PHYSICAL

Cutout diameter (mm) Recessed depth (mm) Construction material Weight (kg) 105 160 Aluminium 0,45

Included

Remote

Electronic

Without

Class II








Light Shooter Fixed No Trim designed by FLOS Architectural


High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.











FLOS

Light Shooter Fixed No Trim . Accessories

Optical





08.8041.68

08.8412.14

Elliptical light distribution lens Honeycomb

Elliptical light distribution lens in 4mm thick tempered glass.

"Honeycomb" anti-glare grid made of aluminium cells.

Light Shooter Fixed No Trim . Lamps




Power LED Lamp category: LED Socket: Special base Lamp type: Power LED



Light Shooter Fixed No Trim designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.





Ø95

