## FLOS

## LIGHT SHOOTER FIXED NO TRIM DIMMABLE

L

Fixed

Symmetric

12° Spot

Included

Number of heads
Mounting
Lamps description
Luminaire luminous flux
Voltage (V)
Environment
Notes

Ceiling recessed Power LED 10W 850 Im 2700K CRI 90 Extreme Cut-off. See reference number 220/240 Indoor LED: All the models include an accessory for IP54. Preinstallation frame included in No Trim versions.

## OPTICAL

Aiming Light distribution symmetry Beam angle

#### ELECTRICAL

Transformer availability Transformer mounting Transformer type

Emergency Insulation class

#### PHYSICAL

Cutout diameter (mm) Recessed depth (mm) Construction material Weight (kg) Remote Electronic, Electronic dimmable, Electronic dimmable I-10V, Electronic dimmable dali Without Class II

) 105 160 Aluminium 0,45








Light Shooter Fixed No Trim Dimmable designed by FLOS Architectural


High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.

03.6529.40.ADA - 3311m White 03.6529.14.ADA - 3311m Black









# FLOS

#### Light Shooter Fixed No Trim Dimmable . Accessories

#### Optical





08.8041.68

08.8412.14

Elliptical light distribution lens

Honeycomb

Elliptical light distribution lens in 4mm thick tempered glass.

"Honeycomb" anti-glare grid made of aluminium cells.

### Light Shooter Fixed No Trim Dimmable . Lamps



Power LED Lamp category: LED Socket: Special base Lamp type: Power LED



Light Shooter Fixed No Trim Dimmable designed by FLOS Architectural

High-performance embedded light fixture for LED light source. Remote 220-240V power supply included.

03.6529.40.ADA - 3311m White
03.6529.14.ADA - 3311m Black

