FLOS

LIGHT SUPPLY ADJUSTABLE TRIM DIMMABLE

L

Adjustable

Symmetric

Included

Remote

Without

Class II

24° Medium

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment

Ceiling recessed Phosphor LED 28VV 3000 Im 4000K CRI 80 Extreme Cut-off. See reference number 220/240 Indoor

Electronic dimmable 1-10V, Electronic dimmable dali

OPTICAL

Aiming Light distribution symmetry Beam angle

ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

PHYSICAL

Cutout diameter (mm) Recessed depth (mm) Construction material Weight (kg) 156 239 Aluminium 1,01








Light Supply Adjustable Trim Dimmable designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

03.6604.40.DA - 1743lm White 03.6604.14.DA - 1743lm Black







ΗÌ

Light Supply Adjustable Trim Dimmable . Accessories


Optical













Light Supply Adjustable Trim Dimmable designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

03.6604.40.DA - 1743lm White 03.6604.14.DA - 1743Im Black



08.8117.68

Flood lens


08.8118.68


Elliptical lens




08.8413.00

Light Supply Adjustable spare reflector. Spot









08.8414.00

Light Supply Adjustable spare reflector. Medium



08.8415.00

Light Supply Adjustable spare reflector. Flood



FLOS

Light Supply Adjustable Trim Dimmable . Lamps




Phosphor LED Lamp category: LED Lamp type: Phosphor LED



Light Supply Adjustable Trim Dimmable designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.





CERTIFICATIONS

