

## LIGHT SUPPLY ADJUSTABLE TRIM

<b>Number of heads</b>	1
<b>Mounting</b>	Ceiling recessed
<b>Lamps description</b>	Phosphor LED 28W 3000 lm 4000K CRI 80
<b>Luminaire luminous flux</b>	Extreme Cut-off. See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor

### OPTICAL

<b>Aiming</b>	Adjustable
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	33° Flood

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Remote
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class II

### PHYSICAL


<b>Cutout diameter (mm)</b>	156
<b>Recessed depth (mm)</b>	239
<b>Construction material</b>	Aluminium
<b>Weight (kg)</b>	1,01





**Light Supply Adjustable Trim**  
designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

● 03.6605.40 - 1725lm	White
● 03.6605.14 - 1725lm	Black



### CERTIFICATIONS



## Light Supply Adjustable Trim . Accessories

### Optical



● 08.8049.14  
**Honeycomb. Small Cells**



● 08.8377.14  
**Honeycomb. Big Cells**



● 08.8242.14  
**Screening crosspiece**



○ 08.8117.68  
**Flood lens**



○ 08.8118.68  
**Elliptical lens**



○ 08.8413.00  
**Light Supply Adjustable spare reflector. Spot**



○ 08.8414.00  
**Light Supply Adjustable spare reflector. Medium**




○ 08.8415.00  
**Light Supply Adjustable spare reflector. Flood**





**Light Supply Adjustable Trim**  
designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

- 03.6605.40 - 1725lm White
- 03.6605.14 - 1725lm Black



### CERTIFICATIONS



## Light Supply Adjustable Trim . Lamps



### Phosphor LED

**Lamp category:**  
LED


**Lamp type:**  
Phosphor LED



### Light Supply Adjustable Trim designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

- 03.6605.40 - 1725lm    White
- 03.6605.14 - 1725lm    Black



### CERTIFICATIONS

