

LIGHT SUPPLY ADJUSTABLE NO TRIM DIMMABLE

Number of heads

Mounting Ceiling recessed

Lamps description Phosphor LED 28W 3000 Im 3000K CRI 80 Luminaire luminous flux Extreme Cut-off. See reference number

Voltage (V) 220/240 **Environment** Indoor

Notes Pre-installation frame or Soft Architecture installation plate

for No Trim installation. Have to be ordered separately.

OPTICAL

Aiming Adjustable Light distribution symmetry Symmetric 24° Flood Beam angle

ELECTRICAL

Transformer availability Included **Transformer mounting** Remote

Electronic dimmable I-10V, Electronic dimmable dali Transformer type

Without **Emergency Insulation class** Class II

PHYSICAL

Cutout diameter (mm) 156 Recessed depth (mm) 239 **Construction material** Aluminium Weight (kg) 1,01






Light Supply Adjustable No Trim Dimmable

designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

03.6616.40.DA - 1742lm White 03.6616.14.DA - 1742lm Black



Ø155

CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com



Light Supply Adjustable No Trim Dimmable . Accessories

Optical









08.8049.14

08.8377.14

08.8242.14

Light Supply Adjustable No Trim Dimmable

Honeycomb. Small Cells

Honeycomb. Big Cells

Screening crosspiece

designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.


















08.8117.68

08.8118.68

08.8413.00



Flood lens

Elliptical lens

Light Supply Adjustable spare reflector. Spot









35°



365°





ΙP

08.8414.00

08.8415.00

23

Light Supply Adjustable spare reflector. Medium Light Supply Adjustable spare reflector. Flood

Flos.architectural@flos.com www.flos.com



Light Supply Adjustable No Trim Dimmable . Accessories

Mounting





08.8119.00

Pre-installation frame So

Pre-installation frame.

SA.6600.1

Soft Architecture installation plate

Soft Architecture installation plate for integration in plasterboard.



Light Supply Adjustable No Trim Dimmable

designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

03.6616.40.DA - 1742lm White
03.6616.14.DA - 1742lm Black


Light Supply Adjustable No Trim Dimmable . Lamps



Phosphor LED
Lamp category:
LED

Lamp type:

Phosphor LED



Ø155

CERTIFICATIONS















IP 23