

## LIGHT SUPPLY FIXED NO TRIM DIMMABLE

<b>Number of heads</b>	1
<b>Mounting</b>	Ceiling recessed
<b>Lamps description</b>	Phosphor LED 28W 3000 lm 4000K CRI 80
<b>Luminaire luminous flux</b>	Extreme Cut-off. See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Pre-installation frame or Soft Architecture installation plate for No Trim installation. Have to be ordered separately.

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Remote
<b>Transformer type</b>	Electronic dimmable I-10V, Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class II

### PHYSICAL


<b>Cutout diameter (mm)</b>	156
<b>Recessed depth (mm)</b>	277
<b>Construction material</b>	Aluminium
<b>Weight (kg)</b>	0,98





**Light Supply Fixed No Trim Dimmable**  
designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

- 03.6625.40.DA - 65° - 1696lm White
- 03.6625.06.DA - 48° - 2270lm Aluminum



### CERTIFICATIONS



## Light Supply Fixed No Trim Dimmable . Accessories


### Mounting



○ 08.8359.00

#### Pre-installation frame

Pre-installation frame.



○ SA.6610.1

#### Soft Architecture installation plate

Soft Architecture installation plate for integration in plasterboard.



**Light Supply Fixed No Trim Dimmable**  
designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

○ 03.6625.40.DA - 65° - 1696lm White

● 03.6625.06.DA - 48° - 2270lm Aluminum

## Light Supply Fixed No Trim Dimmable . Lamps




#### Phosphor LED

#### Lamp category:

LED

#### Lamp type:

Phosphor LED



### CERTIFICATIONS

