

LIGHT SUPPLY WALL-WASHER NO TRIM DIMMABLE

Number of heads	1
Mounting	Ceiling recessed
Lamps description	Phosphor LED 28W 3000 lm 4000K CRI 80
Luminaire luminous flux	Extreme Cut-off. See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Pre-installation frame or Soft Architecture installation plate for No Trim installation. Have to be ordered separately.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Asymmetric

ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic dimmable I-I0V, Electronic dimmable dali
Emergency	Without
Insulation class	Class II

PHYSICAL

Cutout diameter (mm)	155
Recessed depth (mm)	290
Construction material	Aluminium
Weight (kg)	1,01




Light Supply Wall-Washer No Trim Dimmable

designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

- 03.6628.40.DA - 38° - 1918lm White
- 03.6628.06.DA - 35° - 1967lm Aluminum



CERTIFICATIONS



Light Supply Wall-Washer No Trim Dimmable . Accessories

Mounting



08.8137.00

Pre-installation frame

Pre-installation frame.



SA.6615.1

Soft Architecture installation plate

Soft Architecture installation plate for integration in plasterboard.



Light Supply Wall-Washer No Trim Dimmable

designed by FLOS Architectural

Recessed luminaire with integrated Phosphor LED light source. Remote 220/240V driver included.

03.6628.40.DA - 38° - 1918lm White

03.6628.06.DA - 35° - 1967lm Aluminum

Light Supply Wall-Washer No Trim Dimmable . Lamps




Phosphor LED

Lamp category:

LED

Lamp type:

Phosphor LED



CERTIFICATIONS

