

LIGHT SUPPLY WALL-WASHER NO TRIM

Number of heads

Mounting Ceiling recessed

Lamps description LED Array High Performances 33,2W 3770 lm 3000K CRI 80

Luminaire luminous flux Extreme Cut-off. See reference number

Voltage (V) 220/240 Environment Indoor

Notes Pre-installation frame. To be ordered separately.

OPTICAL

Aiming Fixed
Light distribution symmetry Asymmetric

ELECTRICAL

Transformer availability Included
Transformer mounting Remote
Transformer type Electronic
Emergency Without
Insulation class Class II

PHYSICAL

Cutout diameter (mm) 155

Recessed depth (mm) 290

Construction material Aluminium

Weight (kg) 1,01








Embedded luminaire for LED light source. Remote 220/240V power supply included.<nextline>

03.6827.40A - 36° - 2142lm White 03.6827.06A - 34° - 2310lm Aluminum



CERTIFICATIONS











Flos.architectural@flos.com www.flos.com



Light Supply Wall-Washer No Trim . Accessories

Mounting



08.8137.00

Pre-installation frame

Pre-installation frame.

Light Supply Wall-Washer No Trim . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:


LED Array



Light Supply Wall-Washer No Trim designed by FLOS Architectural

Embedded luminaire for LED light source. Remote 220/240V power supply included.<nextline>

03.6827.40A - 36° - 2142lm White 03.6827.06A - 34° - 2310lm Aluminum



CERTIFICATIONS













Flos.architectural@flos.com www.flos.com