FLOS

LIGHT SUPPLY WALL-WASHER NO TRIM

| Number of heads | I |
|-------------------------|--|
| Mounting | Ceiling recessed |
| Lamps description | LED Array High Performances 33,2W 3246 Im 4000K CRI 90 |
| Luminaire luminous flux | Extreme Cut-off. See reference number |
| Voltage (V) | 220/240 |
| Environment | Indoor |
| Notes | Pre-installation frame. To be ordered separately. |

Fixed

Asymmetric

Included

Remote

Electronic

Without

Class II

OPTICAL

Aiming Light distribution symmetry

ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

PHYSICAL

Cutout diameter (mm) Recessed depth (mm) Construction material Weight (kg) 155 290 Aluminium 1,01






Light Supply Wall-Washer No Trim designed by FLOS Architectural

Embedded luminaire for LED light source. Remote 220/240V power supply included.<nextline>

03.6828.40A - 36° - 1845lm White 03.6828.06A - 34° - 1989lm Aluminum





GWT 850°

F

FLOS

Light Supply Wall-Washer No Trim . Accessories

Mounting



08.8137.00

Pre-installation frame

Pre-installation frame.

Light Supply Wall-Washer No Trim . Lamps



LED Array LED Socket: Special base Lamp type: LED Array



Light Supply Wall-Washer No Trim designed by FLOS Architectural

Embedded luminaire for LED light source. Remote 220/240V power supply included.<nextline>

03.6828.40A - 36° - 1845lm White 03.6828.06A - 34° - 1989lm Aluminum

