

## **LIGHT STRIPE 300 MM DIMMABLE I-10V**

**Number of heads** 

**Mounting** Track mounting

Top LED 6W 558 lm 2700K CRI 90 Lamps description

Luminaire luminous flux See reference number

Voltage (V) 48 **Environment** Indoor

Only compatible with DALI, I-10V, FLOS SMART CONTROL profile version. Notes



**Aiming** Fixed Light distribution symmetry Symmetric Beam angle III°



Transformer availability Separate item **Transformer mounting** Remote

Transformer type Electronic dimmable I-10V

**Emergency** Without





Light Stripe 300 mm Dimmable I-I0V designed by FLOS Architectural

Diffused LED light module to be installed in The Tracking Magnet System.

03.8000.14.1V - 244lm Black



## CERTIFICATIONS







Flos.architectural@flos.com www.flos.com



## Light Stripe 300 mm Dimmable I-I0V . Lamps



**Top LED** 

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED




**Light Stripe 300 mm Dimmable I-10V** designed by FLOS Architectural

Diffused LED light module to be installed in The Tracking Magnet System.

03.8000.14.1V - 244lm

Black



## **CERTIFICATIONS**







Flos.architectural@flos.com www.flos.com